

As one popular model of fuel dispensing unit, GI Series are featured with multi functions for payment system, flexible fuel application, more durable upgraded electronic parts etc. to meet various demands of major customers. GI Series are the products, based on traditional excellence, which are upgraded with advanced technology for now and future. It is one of the more popular models preferred by many major clients across the globe for its ease in operation and excellent image to their petrol stations to attract more motorists.



Typical Model GI52GF111B



Typical Model GI52GF212B

**MODEL CODES :**

**Model : GI52GF111B Suction Type\* : 1 hose, 1 product, 2 LCD displays (1 display on each side).**

**Model : GI52GF212B Suction Type\* : 2 hoses, 1 product, 4 LCD displays (2 displays on each side / 2 hoses work simultaneously).**

**Model : GI52GF222B Suction Type\* : 2 hoses, 2 products, 4 LCD displays (2 displays on each side / 2 hoses work simultaneously).**

**Typical Scope of Supply :**

Two sides sheathing with all other panels and lower panel in corrosion resistance powder coated white colour.

- Electro-Mechanical Totalizer.
- Nozzle.
- Breakaway Coupling.
- High Quality Flow Meter.
- Hose Sight Glass.
- Junction Box.
- High Quality Gear Pumping Unit.\*
- High quality Hoses (black color) 3/4" x 3.5m.
- Nozzle swivel is the standard single plane 360 degree type.
- Filter.

(Note : \* Suction Type is suction pump and Remote Type without suction pump is available for STP upon request.)

➤ **Standard Features:**

- More accurate, more durable 4 piston flow meter with own unique technology.
- More durable, long life time and low maintenance.
- Updated electronics interface to any reputable POS and management automation system and self-diagnostic electronic for easy maintenance.
- Large LCD displays for better image with 7 digits for Sale, 6 digits for Liter, 5 digits for Unit Price.

➤ **Standard Specifications:**

- Measurement in liters
- Standard flow rate: 5-50 L/min
- Measurement accuracy:  $\pm 0.25\%$
- Relative humidity: 20% ~ 95%
- Ambient temperature (standard): -20 °C to +55 °C
- Power supply: 3 phase, 380V, 50Hz or 1 phase, 220V 50Hz for motor

➤ **NOTES WHEN ORDERING:**

- Specify its model.
- Specify supply voltage.
- Other useful details or contact us.

---

**TOTAL MEASUREMENT SOLUTIONS PROVIDER**  
**Member of Singapore Manufacturing Federation(Since1932)**

---



Distributed by:

**GROWCO INTERNATIONAL**

**International Business Office :**

**271 Bukit Timah Road, #03-04 Balmoral Plaza, Singapore 259708**

**Tel : (65) 6842 1170**

**Fax : (65) 6842 1182**

**Email: [sales@growco.biz](mailto:sales@growco.biz)**

**Web: [www.growcoin.net](http://www.growcoin.net)**

Growco International reserves the rights, without notice, to alter or improve the designs or specifications of the products described herein.

Origin of Singapore.