

As one popular model of fuel dispensing unit, GI Series is featured with multi functions for payment system, flexible fuel application, more durable upgraded electronic parts etc. to meet various demands of major customers. GI Series are the products, based on traditional excellence, which are upgraded with advanced technology for now and future. It is one of the most popular models preferred by many major clients across the globe for its ease in operation and excellent image to their petrol stations to attract more motorists.



Typical Model GI56QF636A



Typical Model GI56QF632B

MODEL CODES :

Model : GI56GF636A Suction Type* : 6 hoses, 3 products, 6 LCD displays (3 displays on each side / 6 hoses can work simultaneously).

Model : GI56QF636A Remote Type : 6 hoses, 3 products, 6 LCD displays (3 displays on each side / 6 hoses can work simultaneously).

Model : GI56GF632B Suction Type* : 6 hoses, 3 products, 2 LCD displays (1 display on each side / 2 hoses can work simultaneously).

Model : GI56QF632B Remote Type : 6 hoses, 3 products, 2 LCD displays (1 display on each side / 2 hoses can work simultaneously).

Typical Scope of Supply :

Two sides sheathing with all other panels and lower panel in corrosion resistance powder coated white colour with the following related items:

- Electro-Mechanical Totalizer.
- Nozzle.
- Breakaway Coupling.
- High Quality Flow Meter.
- Hose Sight Glass.
- Junction Box.
- Filter.
- High quality Hoses (black color) 3/4" x 3.5m.
- Nozzle swivel is the standard single plane 360 degree type.
- High Quality Gear Pumping Unit (*Suction Pumps Type only).

➤ **Standard Features:**

- More accurate, more durable 4 piston flow meter with own unique technology.
- More durable, long life time and low maintenance.
- Updated electronics interface to any reputable POS and management automation system and self-diagnostic electronic for easy maintenance.
- Large LCD displays for better image (Option with 7 digits for Sale, 6 digits for Liter, 5 digits for Unit Price).

➤ **Standard Specifications:**

- Measurement in liters.
- Standard flow rate: 5-50 L/min.
- Measurement accuracy: ±0.25%.
- Ambient temperature (standard): -20 °C to +55 °C.
- Relative humidity: 20%~95%.
- Power supply: 3 phase, 380V, 50Hz or 1 phase, 220V 50 Hz for motor used in suction pump type.

➤ **NOTES WHEN ORDERING:**

- Specify its model.
- Specify supply voltage.
- Other useful details or contact us.

TOTAL MEASUREMENT SOLUTIONS PROVIDER
Member of Singapore Manufacturing Federation(Since1932)



Distributed by:

GROWCO INTERNATIONAL

International Business Office :

271 Bukit Timah Road, #03-04 Balmoral Plaza, Singapore 259708

Tel : (65) 6842 1170

Fax : (65) 6842 1182

Email: sales@growco.biz

Web: www.growcoin.net

Growco International reserves the rights, without notice, to alter or improve the designs or specifications of the products described herein.

Origin of Singapore.